






Note

1.Allowable axial load and allowable moment load indicated in the spec. sheet are the maximum allowable load when each load is independently activated. Please make sure to consult us in case of combined load at the axial load, radial load, and moment load to be activated, or life of the motor.

2.Please do not wire the pin (A6~B7) which is reserved for encoder manufacturer to avoid the encoder troubles.

3.Special model motor, please refer to the special model drawing.



Nameplate list	
Index	Details
Nameplate 1	UL Motor serial No.1
Nameplate 2	UL Motor serial No.2
Nameplate 3	Encoder type. Resolution
Nameplate 4	Encoder software

Power connector pin assignment			
Pin	Signal	Line color	
1	U	Black	
2	V	Black	
3	W	Black	
4	Ground	Green/Yellow	
Housing : 172167-1 (TEJ)			
Contact : 170364-1 (TEJ)			

Encoder connector pin assignment			
Pin	Signal	Pin	Signal
A1	+5V	A5	N.C.
B1	GND	B5	N.C.
A2	+5V	A6	Reserved
B2	GND	B6	Reserved
A3	SD1	A7	Reserved
B3	SD1*	B7	Reserved
A4	N.C.	A8	FG
B4	N.C.	B8	FG
Housing : J21DPM-16V-KY (JST)			
Contact : SJ2M-002GF-M1.0N (JST)			

Typing side
B1 → B8
A1 → A8
Un-used PINS : A4, A5, B4, B5

Specifications		
Items	Unit	Specifications
Rated torque	N·m	37.9
Max. torque	N·m	90
Rated current	A	6.0
Rated rotation speed	rps	3
Rated output	W	714
Encoder type	Optical absolute (single-turn)	
The signal output	Serial communication	
Interpolation unit	Built-in motor	
Detection pulse	PPR	6,815,744
Electrical detection resolution	arc second	0.191
Allowable moment load	N·m	60
Allowable axial load	N	3,500
Radial runout (No load)	mm	0.05
Axial runout (No load)	mm	0.05
Rotor moment of inertia	kg·m ²	0.022
Mass	kg	10.7
Magnetic pole detection	Absolute position detection	
Power source	ACV	3-phase 200V
Paired servo driver	800W	
Duty type	—	Continuous (S1)
Mounting attitude	—	Horizontal (Rotor facing upward)★
Protection class	IP	40
Operating temperature	°C	0~40
Humidity (Non-condensing)	%	0~85
Vibration resistance	G	1
Withstand voltage	AC 1500V for 1 min. only	
Insulation resistance	Ω	100M or higher

◆ The life of bearing and runout accuracy are different by load condition.
★ Please make sure to consult with us if the mounting is other than horizontal attitude.

NOTE File name/SE-84130A.dwg			ENTRY No. R1-721,76	PRODUCT No. 248-2621
APPROVED			FINISH	MODEL
CHECKED				DISC Motor ND250-55-FSB-UC (ABS) NMR-SEMJA2A-711AB-UC
DESIGNED				TITLE
			MATERIAL	Dimensions (ABS)
			Refer drawing	DRAWING No.
			SCALE 1/2.5	SE-84130A
			third angle projection	REV.
REV. MARK	REV. NOTE	APPROVED	CHECKED	DESIGNED
ENTRY No.		DATE	DATE	DATE
NIKKI DENSO CKD NIKKI DENSO CO., LTD				